

### Mini Thermo Anemometer MT-915V



Mainly used for wind speed, wind temperature measurement engineering, quality control, disease prevention and control and various environmental wind speed, wind temperature measurement

#### FEATURES

- High accuracy, fast response
- Clear LCD display with backlight
- Air velocity and temperature measurement
- MAX/AVG
- Selectable measurement units: m/s, ft/min, MPH, km/hr or knots
- Over range indication
- Battery status indication



#### Specifications

Model	MT-915V		
	Range	Resolution	Accuracy
Air velocity range	0.7~30.0 m/s	< 20.0; 0.1 > 20 ; 1	±( 4% + 2digit)
	2.5~105 km/h		
	1.5~67.0f Mph		
	1.3~58.3 Knots		
Temperature range	-20~70°C/-4~158°F		
Temperature accuracy	± 1.5°C/2.7°F		
Temperature resolution	0.1		
Water proof	IP54		
Air velocity level	1-12		
Data update	1 / second		
Battery life	Around 60 hours		
Auto power off	The meter shuts off automatically after 15 minutes inactivity		
Power supply	3*1.5V “AAA” batteries		
Operating conditions	-20°C ~ 60°C, -4°F ~ 140°F, 10%RH~90%RH		
Storage conditions	-20°C ~ 60°C, -4°F ~ 140°F, 10%RH~75%RH		
Dimension(L*W*H)	178.5*56*30.5mm		
Weight	84g		

### Mini Thermo Anemometer MT-915

#### FEATURES

- Selectable measurement units: ms,ft/min
- MPH, km/hr or knots
- Fast sampling rate
- Color LCD display with backlight
- MAX/MIN/Data HOLD
- Over range indication, low battery indication
- Enable/disable auto power off



#### Specifications

Model	MT-915		
	Range	Resolution	Accuracy
Air Velocity range	0.4~30.0 m/s	0.1	±3%±0.3 m/s
	1.4~108 km/h	0.1	±3%±1.0 km/H
	0.9~67.0f Mph	0.1	±3%±0.4 Mph
	0.8~58.0 Knots	0.1	±3%±0.4 Knots
	80~5900 ft/min	1.0	± 3%±40 ft/min
Temperature range	-20 ~ 70°C /-4 ~ 158°F		
Temperature accuracy	± 1.5°C/2.7°F		
Temperature resolution	0.1		
Operating conditions	-20°C ~ 60°C, -4°F ~ 140°F, 10%RH~90%RH		
Storage conditions	-20°C ~ 60°C, -4°F ~ 140°F, 10%RH~75%RH		
Power supply	3*1.5V “AAA” batteries		
Battery life	Around 60 hours		
Dimension(L*W*H)	178.5*56*30.5mm		
Weight	84g		

